Product datasheet

Specifications



Easy UPS 3M 200kVA 400V 3:3 UPS for external batteries, Start-up 5x8

E3MUPS200KHS

Presentation

Easy-to-install, easy-to-connect, easy-to-use, and easy-to-service 200 kVA 3 phase UPS with advanced product features, robust electrical specifications and compact design making your business continuity easy. Ideal for small and medium data centers and other business critical applications, this UPS is EcoStruxure-ready to give you peace of mind with cloud-based remote monitoring and management. It is supplied without batteries, so you can easily customize your battery solution. Includes 5x8 start-up service.

Lead time

Usually Ships within 6 Weeks

Main

Main Input Voltage	400 V 3 phases
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	380 V 415 V
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V 415 V
Rated power in W	200 kW
Rated power in VA	200 kVA
Provided equipment	Dust filter Installation guide Start-up service
Range of product	Easy UPS 3M

Batteries & Runtime

Efficiency	View Efficiency Graph □
Battery type	External battery system
Number of battery filled slots	0
Number of battery free slots	0

Physical

Colour	White (RAL 9003)
Height	130 cm
Width	60 cm
Depth	85 cm
Net weight	304 kg
USB compatible	Yes

Input

•	
Maximum input current	336 A
Max short time withstand current	10 kA
Input harmonic distortion	Less than 3 % for full load
Load power factor	0.5 leading to 0.5 lagging without derating
Input Power Factor at Full Load	0.99
Input voltage limits	342477 V
Network frequency	4070 Hz

Output

Maximum configurable power in VA	200 kVA
Maximum configurable power in W	200 kW
Output frequency	50 Hz sync to mains 60 Hz sync to mains
Harmonic distortion	Less than 3 %
Output harmonic distortion	< 3% linear load and < 5% non-linear load
Output overload operation	10 minutes at 125% and 60 seconds at 150%
Output voltage tolerance	+/- 1 %
UPS type	Double conversion online
Wave type	Sine wave

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 % non-condensing
Operating altitude	04921 ft
Ambient air temperature for storage	-2555 °C
Storage Relative Humidity	095 % non-condensing
Storage altitude	0.00000000015240.000000000 m
Acoustic level	72 dBA
Heat dissipation	34121 Btu/h
IP degree of protection	IP20

Communications & Management

control panel

Touch screen LCD user interface

Packing Units

V	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	150 cm
Package 1 Width	97.5 cm
Package 1 Length	72.5 cm
Package 1 Weight	338 kg

Contractual warranty

Warranty

1 year on-site repair or replace with factory authorized Start-Up

C Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

${\ensuremath{ \bigtriangledown \bigtriangledown}}$ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	251928
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	Bcc48c21-81f4-41e7-bf2b-336ef659ee43
REACh Regulation	REACh Declaration

Use Again

igodoldoldoldoldoldoldoldoldoldoldoldoldol	
Circularity Profile	End of Life Information
Take-back	No